

3

A Textron Company





Gator[®] Battery-Powered Crimping Tool Low Pressure Crimping Tool High Pressure Remote Crimping Head

FLIP TOP Grimping Ling

More capacity with improved consistency

- Increased crimping capacity of up to 1250 MCM aluminum and 1500 MCM copper color coded lugs and splices.
- No deflection when crimping.
- More stable, symmetrical and consistent due to the enclosed nature of the tool.

Improved usability due to 32% weight reduction

- Weight reduction and improved balance provide less fatigue over time.
- 32% weight reduction versus existing C-head model of the 15 ton crimper.
- The EK Battery version weighs a mere 16.3 lbs.

Safer alternative resulting from enclosed crimping head

- Features Greenlee's patented "Quick Release" spring loaded locking mechanism for faster engagement.
- Uses a self-centering chamfered pin for easy head closure.
- Tool head rotates 350° for ease of operation and user comfort.

MORE CAPACITY UP TO 1250 MCM ALUMINUM AND 1500 MCM COPPER

Gator[®] Battery-Powered 15 Ton Crimping Tool



ARS





15-TON

- Intelli-CRIMP[™] Technology includes a pressure sensor that monitors the crimping force of each crimp and provides the operator a visual and audible alert if the force is below specifications.
- Automatic Retraction Stop (ARS) retracts the ram just enough to get ready for the next cycle, saving time and energy.
- 18V Li-ion battery provides 70% more cycles per charge and faster cycle times.
- Accepts P-style die to crimp splices and lugs up to 1500 kcmil copper and 1250 kcmil aluminum.
- Accepts Greenlee KC12, KA12, and KD12 crimping dies as well as industry U-style dies with optional UA15T adapters.
- Light weight flip-top head with patented quick release locking pin.
- 2" jaw opening.
- Crimping head rotates 350°
- Battery recharges in 28 minutes.

SPECIFICATIONS

Gator[®] Battery-Powered 15 Ton Crimping Tool

Capacity	Color-coded copper lugs and splices: #8 to 1500 kcmil (MCM) color-coded lugs and splices: #8 to 1250 kcmil (MCM)
Crimping Force at 10,000 psi	30,000 lbs (135kN)
Battery	18 V, 3.0 Ah, Li-ion
Weight	16.3 lbs (7.4kg)
Length	18.5" (470mm)
Width	3" (76mm)
Height	13.5" (343mm)

Low Pressure 15 Ton Crimping Tool

High Pressure 15 Ton Remote Crimping Head

15<u>-</u>TON

- No high pressure intensifier required.
- Relief valve signals operator when crimp is complete.
- Accepts P-style die to crimp splices and lugs up to 1500 kcmil copper and 1250 kcmil aluminum.
- Accepts Greenlee KC12, KA12, and KD12 crimping dies as well as industry U-style dies with optional UA15T adapters.
- Light weight flip-top head with patented quick release locking pin.
- 2" jaw opening.
- Crimping head rotates 350°

SPECIFICATIONS

Low Pressure 15 Ton Crimping Tool

Capacity	Color-coded copper lugs and splices: #8 to 1500 kcmil (MCM) color-coded lugs and splices: #8 to 1250 kcmil (MCM)		
System	Open and closed-center hydraulic systems		
Crimping Force at 1,500 psi	30,000 lbs (133.4 kN)		
Operating Pressure	1,500 - 2,000 psi		
Flow Rate	3 - 9 gpm		
Pressure Port	3/4 - 16 SAE 0-Ring		
Return Port	3/4 - 16 SAE 0-Ring		
Weight	25 lbs (11.3kg)		
Length	23.5" (597mm)		
Width	6.5" (165mm)		

15-TON

IMPROVED USABILITY 32% WEIGHT REDUCTION VERSUS EXISTING MODELS



- Accepts P-style die to crimp splices and lugs up to 1500 kcmil copper and 1250 kcmil aluminum.
- Accepts Greenlee KC12, KA12, and KD12 crimping dies as well as industry U-style dies with optional UA15T adapters.
- Light weight flip-top head with patented quick release locking pin.
- 2" jaw opening.
- Operates with 10,000 psi hydraulic sources.
- Equipped with 3/8" male screw-type 10,000 psi coupler.
- Crimping head rotates 350°

SPECIFICATIONS

High Pressure 15 Ton Remote Crimping Head

Capacity	Color-coded copper lugs and splices: #8 to 1500 kcmil (MCM) color-coded lugs and splices: #8 to 1250 kcmil (MCM)		
Crimping Force at 10,000 psi	30,000 lbs (135kN)		
Operating Pressure	10,000 psi		
Weight	11.4 lbs (5.2kg)		
Length	13.75" (349mm)		
Width	3" (76mm)		
Height	5" (127mm)		

(P)

GREENLEE®

UTILITY

ORDERING INFORMATION

(R) = REPLACEMENT PART (A) = ACCESSORY

CAT#	UPC#	DESCRIPTION	QTY			
Ga	tor® Batte	ry-Powered 15 Ton Crimping Tool				
EK1550FTLU11	00788	15 Ton, Flip Top, Battery Powered Crimping Tool with 120 V Charger	1			
EK1550FTLU12	00789	15 Ton, Flip Top, Battery Powered Crimping Tool with 12 V Charger	1			
EK1550FTLU22	00902	15 Ton, Flip Top, Battery Powered Crimping Tool with 230 V Charger	1			
EK1550FTLU120	00790	15 Ton, Flip Top, Battery Powered Crimping Tool with 120 V AC Adapter	1			
EK1550FTLU230	00792	15 Ton, Flip Top, Battery Powered Crimping Tool with 230 V AC Adapter	1			
UA15T	00260 🔕	Die-Adaptors - Greenlee "U" style dies, Burndy "U" style dies, Ilsco ILD style dies, T&B 15500 style dies, Blackburn 15500 style dies	1			
23492	23492 🚯	Handle	1			
52176	52176 🔕	18V, 3.0 Ah, Li-ion Battery	1			
52178	52178 🔇	120V Charger	1			
52179	52179 🚺	230V Charger	1			
52180	52180 🔇	12V Charger	1			
Low Pressure 15 Ton Crimping Tool						
LPK1550FT	00490	15 Ton, Flip Top, Low Pressure Crimping Tool	1			
UA15T	00260 ()	Die-Adaptors - Greenlee "U" style dies, Burndy "U" style dies, Ilsco ILD style dies, T&B 15500 style dies, Blackburn 15500 style dies	1			
23492	23492 🔕	Handle	1			
High Pressure 15 Ton Remote Crimping Head						
RK1550FT	00552	15 Ton, Flip Top, Remote Head Crimping Tool	1			
UA15T	00260 🔕	Die-Adaptors - Greenlee "U" style dies, Burndy "U" style dies, Ilsco ILD style dies, T&B 15500 style dies, Blackburn 15500 style dies	1			
23492	23492 🙆	Handle	1			

LEGEND OF FEATURES



Works well with others

- The new flip-top head is directly compatible with P" style dies (no adaptor required)
 - Incorporates a more industry standardized "U" style adaptor (UA15T)
 - The EK1550FTLU and RK1550FT tools are UL and CUL classified
 - with Anderson[®], Blackburn[®], Burndy[®], ILSCO[®],
 - Panduit[®], Penn-Union[®] and Thomas and
 - Betts[®] copper and aluminum color coded lugs and splices when used with UA15T die adaptors and with Greenlee KC12 and KA12 crimping dies.



UA15T



WWW.Greenlee.Com MA-5784 06/12 4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070 ©2012 Greenlee Textron Inc. • An ISO 9001 Company • Printed in USA Greenlee Textron Inc. is a subsidiary of Textron Inc.